

« RIGID WATER TRUCKS

SPECIALISED SUPPORT EQUIPMENT



ETT WATER TRUCKS

Engineered from the ground up, ETT Water Trucks make use of high-quality components and superior manufacturing techniques to ensure seamless performance in the toughest conditions.

Over years of design, development and improvement, ETT Water Trucks have earned the reputation for being the most durable and reliable equipment in the field.

Compatible with all major OEM Rigid Truck models, our tank capacities range from 36 000L to 230 000L.



ULTRA LOW CENTRE OF GRAVITY

Boasting the lowest centre of mass in the industry, our tanks are designed to conform to dynamic payload ratings to ensure machine handling in motion will remain nominal.



CUSTOM CONFIGURATIONS

All ETT Water Trucks can be configured to customer requirements. We stock an array of attachments designed to provide custom solutions for individual application.



CORROSIVE PROTECTION

Maximum corrosion protection: Special internal and external coatings provide protection from salt water, corrosive chemicals and acidic mining water.



SURGE CONTROL

The ETT internal baffle system forms the core of all our water tanks, designed for maximum tank rigidity and longevity whilst ensuring minimal fluid surge and slosh.



WORLD CLASS COMPONENTS

All outsourced components are obtained from reputable manufacturers. Having exceptional relations with all our suppliers is key to our ability to deliver a complete product that is unmatched in quality and durability.



CDR SPRAY SYSTEM

The ETT CDR (Constant Deposition Rate) is designed to distribute water to a road surface in a controlled manner to achieve consistent spray coverage, regardless of the truck travel speed.

OPTIONAL FEATURES

Our tailor-made solutions include a choice between manual or remote operated water cannons, as well as fixed or variable aperture spray heads, a ground penetration Spray Bar, and an internal Foam Tank for firefighting.

OPTIONAL WATER CANNON

Our Water Cannons consist of industrial grade stainless-steel construction. High-quality seals ensure reliable operation in the most extreme environments associated with the corrosive properties of mine water.



WATER TANK CAPACITY CONFIGURATIONS

RIGID TRUCK	CAPACITY LITRES	CAPACITY US GALLONS	PUMP FLOW
40 Ton	36 000 L	9 500 gal.	3 000 Lpm
60 Ton	50 000 L	13 200 gal.	3 000 Lpm
70 Ton	60 000 L	15 850 gal.	3 000 Lpm
100 Ton	76 000 L	20 000 gal.	6 400 Lpm
150 Ton	115 000 L	30 400 gal.	6 400 Lpm
200 Ton	150 000 L	39 600 gal.	6 400 Lpm
250 Ton	180 000 L	47 500 gal.	2 x 6 400 Lpm
400 Ton	230 000 L	60 800 gal.	2 x 6 400 Lpm

25+
years' service
in the harshest

environments



ETT maintains a complete inventory of repair and maintenance parts for all of our products to include accessory kits and service parts packages. Our professionally trained team of engineers and support staff are focused on ensuring your asset's optimal performance and ultimately your satisfaction with ETT products.

Under our policy of continuous improvement, we reserve the right to change technical data and design without prior notice. Photographs featured in this brochure may include optional equipment.



www.ett.com





ISO CERTIFIED







SERVICE

SPARES













